

Accessories for fire and gas alarm control systems

These accessories are common products for all intelligent analogue addressable fire alarm systems and conventional fire alarm systems with Mavigard and Maxlogic brands.

Features

01. Electronic sounders and electronic sounder strobes are compatible with EN 54-3, manual call points are compatible with EN 54-11 and power supply units are compatible with EN 54-4
02. Electronic sounders and sounder strobes provide 105 dB(A) @ 24 V DC max. audible signal power
03. Electronic fire alarm bells having 150 mm diameter provide strong audio power



MG-5100 Conventional manual call point with break-glass

The MG-5100 MCP is activated by manual breaking of the film-coated glass which does not harm fingers. When the glass is broken, the switch, normally resting on glass edge, changes position.



MG-5120 Conventional manual call point, resettable

The MCP is activated by manual pressing on the flexible plastic cover. The switch, normally resting on flexible plastic cover, changes position and retains it until it is brought into its initial position. MG-5130 MCP is weather-proof (IP67) and can be used in outdoor applications.



MG-4000 Remote indicator

Remote indicators facilitate identifying the alarm location by matching the triggered detector placed above false ceiling or rooms.



Power supply units

Switched mode power supplies have models with 24 V DC, 2.5A, 4A, 5A ve 10A output currents. The power supplies are microprocessor controlled and perform continuous fault monitoring (earth, batteries, 24 V DC, 220 V mains fail etc.).



MG-5000 Electronic sounder

MG-5200 Electronic sounder strobe

The maximum audible signal power of the sounder is 105 dB(A) 24 V DC at 1 m. and the sounders are for indoor use. The strobe has 3 W power and a flash rate of 150/min.



MG-5400 Fire alarm bell (6 inches)

The bell is designed to meet requirements of superior performance with low current consumption. A built-in varistor suppression element is incorporated to micro-motor unit of the bell to reduce EMI and RFI effects.

ACCESSORIES MODELS	
Product code	Description
MG-4000	Remote indicator
MG-4100	Remote indicator mounting box
MG-5100	Manual call point, break-glass
MG-5120	Manual call point, resettable
MG-5130	Manual call point, weather-proof (IP67)
MG-5000	Electronic sounder, red, 12 / 24 V DC
MG-5200	Electronic sounder strobe, red, 12 / 24 V DC
MG-5400	Electronic fire bell, red, 24 V DC, 150mm
MG-7050	Mavigard SMPS switched mode power supply unit 2.5A
MG-7080	Mavigard SMPS switched mode power supply unit 4A
ML-0515	Maxlogic SMPS switched mode power supply unit, 5A
ML-05110	Maxlogic SMPS switched mode power supply unit, 10A

